



SatSENS.door

For the detection of the status of doors and rolling shutters (open / closed) we offer you the SatSENS.door. It is characterized by high tamper resistance and failure safety as well as accuracy in the analysis of the status. In addition, this sensor has a resistant polycarbonate housing and is thus protected against water jets and dust.

The SatSENS.door is excellently suited for fixed installation in trailers, for example, where it demonstrates its strength through extreme stability and contact range. It has special manipulation cables in the connection to be able to detect and report corresponding manipulation or damage.

Like all sensors of the SatSENS family, you can also connect the Sat SENS.door to any SatMOS® system and thus expand a simple telematics system to a monitoring system for doors or rolling gates.

Strengths at a glance

- Robust design for rough use
- Tamper-proof due to special loop cable in the connection
- High reliability with large contact range
- Connectable to devices of the Sat MOS® family and third-party suppliers

Technical data

- Housing: polycarbonate, 2-piece
- Connection: 1m cable, 4-wire, open end
- Dimensions (contact): 85 x 38 x 13 mm (length x width x height)
- Dimensions (magnet): 50 x 26 x 25 mm (length x width x height)
- Protection class: IP65
- contact range: approx. 25mm
- Working temperature: -10°C / +60°C
- Approval: EN50131-2-6 IMQ

